

# Basic SQL

---

---

---

---

---

---

---

---


# Relational Database Languages

Tuple relational calculus

- ALPHA (Codd, 1970s)
- QUEL (based on ALPHA)
- Datalog (rule-based, like PROLOG)

Domain relational calculus

- QBE (used in Access)



---

---

---

---

---

---

---

---

# History of SQL

Standards:

- SQL-86 (ANSI, ISO)
  - SQL-89
  - SQL-92 (SQL2)
  - SQL:1999 (SQL3)
  - SQL:2003
  - SQL:2006
  - SQL:2008
  - SQL:2011
- IBM developed SEQUEL in early 70s  
(Structured English Query Language)  
Renamed SQL  
(Structured Query Language)

Many different flavors of SQL:  
sqlplus, SQLServer, MySQL, etc.

**Here:** Oracle SQL

---

---

---

---

---

---

---

---

## Parts of SQL

### DDL

Creating (CREATE),  
Modifying (ALTER), and  
Removing (DROP)

Catalogs  
Schemas  
Relations (Tables)  
Constraints  
Domains  
Triggers

### DML

Retrieving (SELECT),  
Inserting (INSERT),  
Modifying (UPDATE), and  
Removing (DELETE).

### DCL

Grant privileges (GRANT)  
Revoke privileges (REVOKE)

---

---

---

---

---

---

---

---

## SELECT

Combination of select and project operations.

Basic Syntax:

```
SELECT attribute_list
FROM table_list
WHERE condition
GROUP BY attribute_list
HAVING condition
ORDER BY attribute_list;
```

Example:

```
SELECT LastName, SID
FROM student
WHERE career = 'UGRD' AND
started < 2008;
```

---

---

---

---

---

---

---

---

## SELECT \* and empty WHERE

```
SELECT *
FROM student;
```

```
SELECT *
FROM student, studentgroup;
```

```
SELECT *
FROM student, studentgroup
WHERE presidentID = SID
```

---

---

---

---

---

---

---

---

## SELECT Examples

University

- List the SSNs of all students
- List all names of all student groups
- List the names of all programs
- List the name of all students in the IT department

---

---

---

---

---

---

---

---

## Duplicates in SQL

Duplicates can occur if no key attribute is selected

SQL keeps duplicates, for several reasons:

- Cheaper to implement  
(duplicate elimination is expensive)
- Duplicates might be required  
(e.g., aggregate functions)

Removal of duplicates can be forced using `DISTINCT`

`SELECT DISTINCT`      `SELECT ALL`

Example:

List cities in which students live (university).

---

---

---

---

---

---

---

---

## Excursion: How to write SQL Queries

---

---

---

---

---

---

---

---

## How to Write Simple SQL Query

### 3 Stages

Before you write the SQL

Writing the SQL

After Writing the SQL

---

---

---

---

---

---

---

---

## Before you write the SQL

Make sure you **understand** the problem.  
Clarify if necessary

Do it by **hand**.  
Reflect on what you did.

---

---

---

---

---

---

---

---

## Writing the SQL

Start with **FROM**  
which tables are involved, how often?

Then do **WHERE**  
first join all tables (n tables need n-1 equals) - test  
then add particular conditions

Finally, do **SELECT**  
What info do you need to display

---

---

---

---

---

---

---

---

## After Writing the SQL

Test

Run the query

Compare output to what you expected  
sanity check: does it make sense?

In case of problems: read query

---

---

---

---

---

---

---

---

## End of Excursion

---

---

---

---

---

---

---

---

## Renaming (Aliases)

If necessary we can rename attributes:

```
SELECT LastName || ', ' || FirstName AS Name  
FROM student;
```

and tables (drop AS in Oracle for table renaming)

```
SELECT S.Lastname, SG.Name  
FROM student AS S, studentgroup AS SG  
WHERE S.SID = SG.PresidentID;
```

---

---

---

---

---

---

---

---

## Renaming Examples

University

- List the names of all students and expected graduation year
- List the names of student groups and the names of their presidents

---

---

---

---

---

---

---

---

## Conditions

=	Equality
<	Less than
<=	Less than or equal
>	Greater than
>=	Greater than or equal
<> or !=	not equal (depends on system)
LIKE	Allows Wildcards (Oracle) % (any number of characters) _ (single character)

Also (Oracle): REGEXP\_LIKE (text, pattern)

---

---

---

---

---

---

---

---

## Operators

+	Addition (works for dates in Oracle/Access)
-	Subtraction (works for dates in Oracle/Access)
*	Multiplication
/	Division
	Concatenation (for strings)
and, or, not	Boolean operations

---

---

---

---

---

---

---

---

## Functions (Oracle) Strings and Numbers

String type:  
Length(s)                      Length of string s  
Rtrim(s), Ltrim(s)          Delete trailing (leading) spaces

Numeric type:  
Round(x)                      Round x to integer  
Round(x,k)                  Round x to k positions  
Abs(x)                        Absolute value of x  
Exp(x)                         $e^x$

See [http://download.oracle.com/docs/cd/B19306\\_01/server.102/b14200/functions.htm#i1482196](http://download.oracle.com/docs/cd/B19306_01/server.102/b14200/functions.htm#i1482196)

---

---

---

---

---

---

---

---

## Functions (Oracle) Date/Timestamp

extract                      date to integers  
last\_day                    last day of month  
months\_between          months between two dates  
  
to\_char(date, fmt)      format date (e.g. MM, MON, MONTH)

```
SELECT extract (year from current_date)
FROM dual;
```

---

---

---

---

---

---

---

---

## Between and Ordering

For number types, ranges can be defined using BETWEEN.

```
SELECT LastName, SID
FROM student
WHERE started between 2001 and 2003;
```

The ORDER BY clauses allows ordered output  
multiple attributes, expressions allowed  
ASC (default) and DESC to specify order

```
SELECT LastName, SID      SELECT LastName, SID
FROM student              FROM student
ORDER BY started ;        ORDER BY started DESC, LastName;
```

---

---

---

---

---

---

---

---

# Truth and Tables

Post: *A General Theory of Elementary Propositions.*

$p$	$\neg p$	$p, q$	$p \vee q$
+	-	++	+
-	+	+-	+
		-+	+
		--	-

$p, q$	$p \wedge q$
++	+
+-	-
-+	-
--	-

Definition: A function is a *truth-function* iff its truth only depends on the truth of its arguments.

Theorem (Post): Every truth-function can be written using only negation and disjunction. (Or negation and conjunction.)

---

---

---

---

---

---

---

---

# Logic examples I

- Students in computer science and information systems
- Graduate students unless they are PhDs.
- List all graduate students in computer science, computer gaming and information systems.
- List graduate and undergraduate students not from Chicago that started before 2010 and after 2012.
- List courses that violate the rule: All gaming courses must be 300 or above, all computer science courses must be 400 or above and IT courses must be at most 200 level.
- Check whether there are students that violate the following rules: Computer gaming students must be undergraduates, information system students must be graduates.
- List students that violate the rule: A PhD student cannot be an undergraduate.

---

---

---

---

---

---

---

---

# Logic examples II

- List students that have both a graduate and an undergraduate record (go by name).
- List courses that have both grad and undergrad versions (go by title).
- List students that don't have a SSN listed.
- List years in which no undergraduate computer science student started.

---

---

---

---

---

---

---

---



## Logic examples II

- List students that have both a graduate and an undergraduate record (go by name).
- List courses that have both grad and undergrad versions (go by title).
- List students that don't have a SSN listed.
- List years in which no undergraduate computer science student started.

Some of these we can't do yet (4), for some we need additional knowledge (3), and some we can do (1,2) but there must be better solutions.

---

---

---

---

---

---

---

---

## Nulls

Reasons:

- we don't know value
- value isn't applicable
- we don't know whether value is applicable

Null is not a value (well), to test for it use  
is null  
is not null

Examples:

- List students that don't have a SSN listed.
- List studentgroups that don't currently have a president.
- List students that do have a SSN listed.
- We require that students that don't have a last name do enter a first name. List students that violate this requirement.

---

---

---

---

---

---

---

---

## Nulls in Conditions

Example

```
SELECT * FROM student WHERE SSN = 123123123;  
SELECT * FROM student WHERE NOT(SSN = 123123123);
```

?

---

---

---

---

---


---

---

---

# Three-valued Logic

$p$	$q$	$p \text{ OR } q$	$p \text{ AND } q$
True	True	True	True
True	Unknown	True	Unknown
True	False	True	False
Unknown	True	True	Unknown
Unknown	Unknown	Unknown	Unknown
Unknown	False	Unknown	False
False	True	True	False
False	Unknown	Unknown	False
False	False	False	False



$\bar{Q}$	$Q \vee R$	$Q \& R$
$R \text{ t f u}$	$R \text{ t f u}$	$R \text{ t f u}$
$Q \text{ t f f}$	$Q \text{ t t t t}$	$Q \text{ t t f u}$
$f \text{ t t}$	$f \text{ t f u}$	$f \text{ f f f}$
$u \text{ u u}$	$u \text{ t u u}$	$u \text{ u f u}$

$p$	NOT $p$
True	False
Unknown	Unknown
False	True

WHERE conditions: have to be true  
CHECK constraints: can't be false

---

---

---

---

---

---

---

---

---

---

# Nulls in Expressions

## Null in Operations

$\text{null} \circ x = \text{null}$  ( $\circ$  operation like  $+$ ,  $-$ ,  $*$ ,  $/$ , etc.)

```
SELECT EmpID, salary * (1 + level * .05)
FROM employee;
```

## Null in Functions

$f(\dots, \text{null}, \dots) = \text{null}$  (for most functions  $f$ , not all, e.g.  $\parallel$ )

```
SELECT least(price_new, price_used)
FROM bookwprices;
```

Solution: `coalesce(x, y, z, ...)` evaluates to first non-null value

---

---

---

---

---

---

---

---

---

---

# Objections to Nulls

- we don't know what the Null value represents  
Codd suggested two values:  
Missing Applicable/Missing Inapplicable
- 3-valued behavior is counterintuitive and leads to SQL programs behaving incorrectly in presence of Nulls
- wastes space (needs extra indicator bit)

E.g., see the Third Manifesto: [http://en.wikipedia.org/wiki/The\\_Third\\_Manifesto](http://en.wikipedia.org/wiki/The_Third_Manifesto)

---

---

---

---

---

---

---

---

---

---

# Date's Example

Now I can present my argument. The fundamental point I want to make is that certain boolean expressions—and therefore certain queries in particular—produce results that are correct according to three-valued logic but not correct in the real world. By way of example, consider the (nonrelational) database shown in Figure 4-2, in which “the CITY is null” for part P1. Note carefully that the empty space in that figure, in the place where the CITY value for part P1 ought to be, stands for *nothing at all*: conceptually, there’s *nothing at all*—not even a string of blanks or an empty string—in that position (which means the “tuple” for part P1 isn’t really a tuple, a point I’ll come back to near the end of this section).

Figure 4-2. A nonrelational database, with a null

S	SNO	CITY
	S1	London

P	PNO	CITY
	P1	

Consider now the following (admittedly rather contrived) query on the database of Figure 4-2: “Get (SNO,PNO) pairs where either the supplier and part cities are different or the part city isn’t Paris (or both).” Here’s an SQL formulation of this query:

```
SELECT S.SNO, P.PNO
FROM S, P
WHERE S.CITY <> P.CITY
OR P.CITY <> 'Paris'
```

From Chris Date: SQL and Relational Theory, O'Reilly, 2009.

---

---

---

---

---

---

---

---

---

---